

# Sediment 101

---

The San Francisco Bay Area is facing rising sea levels, the rate of which will accelerate in the coming century. Sea level rise threatens public safety and recreation, regional economic productivity, and wildlife that live in and adjacent to the Bay. Restoring and enhancing the Bay's wetlands will help the region adapt to sea level rise, increase flood water absorption, protect critical infrastructure, and create habitat for wildlife.

Restoring and enhancing wetlands and keeping them healthy and elevated as sea level rises will require human intervention to ensure the required amount of sediment and soil reaches them. From 2023-2024, the Sediment and Beneficial Reuse Commissioner Working Group of the San Francisco Bay Conservation and Development Commission held a series of meetings at which local industry experts presented about how best to accomplish this task. Attendees heard from scientists, engineers, agencies, and restoration practitioners about the processes controlling the natural movement of sediment in the estuary, the historic impacts of human activities on sediment flows, and the methods and opportunities available to restore regional wetlands.

This document provides a short summary of what we learned.

## **The sediment in the estuary has varying characteristics that, along with the bathymetry and morphology of the Bay, influence its distribution.**

Different types of sediment are found all throughout the Bay system, with the majority being fine-grained (clay, silt, and mud) and a smaller portion being coarse-grained.<sup>1-3</sup>

These sediments come from the Sacramento-San Joaquin River Delta, the San Francisco Bay, exchange with the Pacific Ocean at the Golden Gate, upland construction, and local flood and stormwater control systems.<sup>4</sup>

The geomorphology and bathymetry of San Francisco Bay varies and includes deep water channels, embayments, shallow shoals, headland "pinch points" that constrain water and sediment flow, intertidal mudflats, tidal wetlands, and sandy beaches.<sup>3</sup>

Different embayments in the Bay have different conditions and ranges of salinity.<sup>3</sup> Sediment is transported in and out of embayments<sup>3,4</sup> and can reverse directions depending on conditions.<sup>5</sup> Wind, tides, currents, salinity, and sediment size and weight also influence how and where sediment will move.<sup>1,6-8</sup>

Finer sediments cycle between the sediment bed and the water column and are easily moved through water movement. Coarser particles require more energy and move along the bottom of the Bay and tributaries. Both fine-grained and coarse-grained sediments travel further distances during high water flows.<sup>9</sup> In tributaries, coarser-grained sediment is often trapped.

## **Sediment flows through the estuary to establish and maintain estuarine wetlands.**

Suspended sediment is naturally transported onto marshes through tidal creeks and across the Bay-marsh edge.<sup>11,12</sup>

Winter storms bring sediment towards marshes where it accumulates near the marsh edge until gentler summer waves transport it up and onto the marsh.<sup>13</sup>

Sediment-laden water is carried onto marshes during flood tide, the sediment then settles out, and water with lower suspended sediment concentration exits marshes during ebb tide. Depending on the strength of the ebb tide, sediment is drawn back out of the marsh or remains in place.<sup>11,13</sup>

## **Human activity since the Gold Rush has altered these sediment flows.**

Human activity has impacted the sediment transport system in the Bay starting with the increase in hydraulic mining during the California Gold Rush of the 1850's which flushed a significant amount of sediment from the Sierra Mountains into the Delta and Bay.<sup>2</sup> That sediment has largely moved through and out of the Bay system.<sup>2</sup>

In the modern era, the development of dams, reservoirs, flood protection projects, and stormwater retention systems disrupted the Bay's natural water flow and sediment system, reducing the amount of sediment entering the Bay.<sup>1,2,9,14-18</sup>

Most of the suspended sediment supply now comes from local tributaries.<sup>14,19,20</sup>

The watershed, dredging, and construction projects will likely supply more material for the maintenance and restoration of wetland habitats across the region than tributaries and rivers.<sup>27</sup>

## **Wetlands provide many benefits to the region.**

Healthy tidal marshes offer sea level rise resilience and essential wildlife habitat.<sup>21,22</sup> Tidal marshes protect shorelines by absorbing flood waters, reducing wave impacts,<sup>23</sup> and mitigating greenhouse gases through carbon sequestration.<sup>24</sup> Healthy marshes also provide sense of place, recreational and educational opportunities, and connect Native Americans to their traditional land.

## **The estuary once had large wetlands that have mostly been destroyed by postcolonial human activity.**

The Bay has deeply subsided baylands (areas of marshes that were historically diked off from the Bay) that require large volumes of sediment to restore elevations necessary for marshes to revegetate.<sup>25</sup> Existing and restored tidal marshes depend on a robust sediment supply to adapt to sea level rise.<sup>26</sup> Due to the aforementioned human interventions, very few Bay marshes are still connected to local tributaries.<sup>10</sup>

## Wetland restoration is accomplished through the beneficial reuse of sediment.

Sediment is removed from the Bay primarily through dredging to maintain navigational channels, mining sand for the construction industry, and maintaining floodwater flows in the lower portions of flood control channels.<sup>2,3,27-30</sup>

Beneficial reuse, a human intervention, is the application of dredged sediment and upland construction soil to restore subsided baylands and maintain wetlands' resilience to sea level rise.<sup>27,34-36</sup>

Between 1.5 and 3 million cubic yards of sediment is dredged for navigation purposes annually from the Bay<sup>30,31</sup> and most is available for marsh restoration through beneficial reuse.

Between 2000 and 2020, 60% of sediment dredged from the Bay was disposed of as waste at regulated disposals sites in the Bay and in the deep ocean.<sup>4</sup>

The method by which sediment and soil are transported to restoration sites depends on the material's characterization, the shallowness of the Bay, and proximity to the sites.<sup>27</sup>

Sediment dredged from navigation channels can be transported in barges that hold between 300 to 6,000 cubic yards. Barges can carry sediment long distances, where the sediment can be offloaded at restoration sites.<sup>32</sup> Trucks bring soil directly from the construction site to the restoration site with loads of 10 to 20 cubic yards per truck. Excess construction soil is used in restoration sites for structural needs or as general fill to raise elevations.<sup>33</sup>

Different types of sediment and soil are required for different types of projects depending on conservation and restoration needs. For example, fine-grained sediment is ideal for mudflats and marsh development, while a mix of fine and coarse grained is ideal for beaches and levees.<sup>16</sup>

To be used at a restoration site, sediment and soil need to be tested to ensure they do not have elevated levels of contamination that would harm wildlife. Dredged sediment and upland construction soil have an established testing program.<sup>33</sup>

## Sea level rise will drown wetlands unless sediment is provided.

Recent climate modeling indicates that there are generally two likely climate scenarios in which there are longer periods of dryness, or longer periods of wetness.<sup>27</sup> The smallest sediment flows, both into and out of the Bay, occur during the dry seasons of wet years. Currently, the Bay experiences the most sediment flow during the wet seasons of wet years, when the most sediment is deposited by tributaries.<sup>3,19</sup>

Without a consistent and robust sediment supply, rising sea levels will inundate marshes over time, threatening their health and the wildlife that they support.<sup>13,24,37-39</sup>

The Bay will need up to 550 million metric tonnes of sediment and soil to preserve, restore, and sustain wetland habitat, and adapt to rising sea levels through 2100.<sup>27</sup>

## References

1. Schoellhamer, D. H. (2011). Sudden clearing of estuarine waters upon crossing the threshold from transport to supply regulation of sediment transport as an erodible sediment pool is depleted: San Francisco Bay, 1999. *Estuaries and Coasts*, 34(5), 885-899.
2. Barnard, P. L., Schoellhamer, D. H., Jaffe, B. E., & McKee, L. J. (2013). Sediment transport in the San Francisco Bay coastal system: an overview. *Marine Geology*, 345, 3-17.
3. BCDC (Bay Conservation and Development Commission) (2016). Central San Francisco Bay Regional Sediment Management Plan. A report prepared by the San Francisco Bay Conservation and Development Commission. 168p. Available from: <https://bcdc.ca.gov/wp-content/uploads/sites/354/2023/09/CentralSFBayRSMPlan.pdf>
4. McKnight, K; Braud, A; Dusterhoff, SD; Grenier, L; Shaw, S; Lowe, J; Foley, MM; McKee, LJ. 2023. Conceptual Understanding of Fine Sediment Transport in San Francisco Bay. SFEI Contribution No. 1114. San Francisco Estuary Institute: Richmond, CA.
5. Schoellhamer, D. H., & Burau, J. R. (1998). Summary of findings about circulation and the estuarine turbidity maximum in Suisun Bay, California (No. 047-98). US Geological Survey.
6. Lacy, J. R., Schoellhamer, D. H., & Burau, J. R. (1996). Suspended-solids flux at a shallow-water site in South San Francisco Bay. In *Proceedings of the North American water and environment congress*.
7. Schoellhamer, D. H. (2002). Variability of suspended-sediment concentration at tidal to annual time scales in San Francisco Bay, USA. *Continental Shelf Research*, 22(11-13), 1857-1866.
8. Brand, A., Lacy, J. R., Hsu, K., Hoover, D., Gladding, S., & Stacey, M. T. (2010). Wind-enhanced resuspension in the shallow waters of South San Francisco Bay: Mechanisms and potential implications for cohesive sediment transport. *Journal of Geophysical Research: Oceans*, 115(C11).
9. McKee, L.J., Zi, T., Pearce, S.A., Grosso, C., Wong, A., Weaver, M., Dusterhoff, S., Lowe, J., Elias, E., Roelvink, F., (2023). Sand budget and sand transport in San Francisco Bay. A report prepared by SFEI-ASC for the State Coastal Conservancy (SCC), and the San Francisco Bay Conservation and Development Commission (BCDC). SFEI Contribution #1125. Richmond, CA.
10. San Francisco Estuary Institute-Aquatic Science Center (2017). Changing Channels: Regional Information for Developing Multi-benefit Flood Control Channels at the Bay Interface. A SFEI-ASC Resilient Landscape Program report developed in cooperation with the Flood Control 2.0 Regional Science Advisors, Publication #801, San Francisco Estuary Institute-Aquatic Science Center, Richmond, CA.
11. Lacy, J. R., Schile, L. M., Callaway, J. C., & Ferner, M. C. (2015). Mechanisms of sediment flux between shallows and marshes. In *The Proceedings of the Coastal Sediments 2015*.
12. Lacy, J. R., Foster-Martinez, M. R., Allen, R. M., Ferner, M. C., & Callaway, J. C. (2020). Seasonal variation in sediment delivery across the bay-marsh interface of an estuarine salt marsh. *Journal of Geophysical Research: Oceans*, 125(1), e2019JC015268.

13. Lacy, J. (2023, May 19). "Sediment supply to San Francisco Bay salt marshes" [Zoom On-line PowerPoint presentation]. Sediment and Beneficial Reuse Commissioner Working Group for the Sediment Wetland Adaptation Project, San Francisco, CA.
14. Schoellhamer, D. H., Wright, S. A., & Drexler, J. Z. (2013). Adjustment of the San Francisco estuary and watershed to decreasing sediment supply in the 20th century. *Marine Geology*, 345, 63-71.
15. Milligan, B., Maly, T., Holmes, R. (2015). "The Pulse, the Sink, and the Shortfall." *Ground Up 04: Out West*.
16. Milligan, B., & Holmes, R. (2017). Sediment is critical infrastructure for the future of California's Bay-Delta. *Shore & Beach*, 85(2), 2.
17. Fregoso, T.A., Foxgrover, A.C., and Jaffe, B.E. (2023), Sediment deposition, erosion, and bathymetric change in San Francisco Bay, California, 1971–1990 and 1999–2020 (ver. 1.1, June 2024): U.S. Geological Survey Open-File Report 2023–1031, 19 p., <https://doi.org/10.3133/ofr20231031>.
18. Wright, S. A., & Schoellhamer, D. H. (2004). Trends in the sediment yield of the Sacramento River, California, 1957–2001. *San Francisco estuary and watershed science*, 2(2).
19. McKee, L. J., Lewicki, M., Schoellhamer, D. H., & Ganju, N. K. (2013). Comparison of sediment supply to San Francisco Bay from watersheds draining the Bay Area and the Central Valley of California. *Marine Geology*, 345, 47-62.
20. Pearce, S., McKee, L., Whipple, A., and Church, T. (2021). Towards a Coarse Sediment Strategy for the Bay Area. SFEI Publication # 1032. San Francisco Estuary Institute-Aquatic Science Center, Richmond, CA.
21. Goals Project (1999). Baylands Ecosystem Habitat Goals. A report of habitat recommendations prepared by the San Francisco Bay Area Wetlands Ecosystem Goals Project. U.S. Environmental Protection Agency, San Francisco, Calif./S.F. Bay Regional Water Quality Control Board, Oakland, Calif.
22. Goals Project (2015). The Baylands and Climate Change: What We Can Do. Baylands Ecosystem Habitat Goals Science Update 2015 prepared by the San Francisco Bay Area Wetlands Ecosystem Goals Project. California State Coastal Conservancy, Oakland, CA.
23. Barbier, E. B., Hacker, S. D., Kennedy, C., Koch, E. W., Stier, A. C., & Silliman, B. R. (2011). The value of estuarine and coastal ecosystem services. *Ecological monographs*, 81(2), 169-193.
24. Callaway, J. C., Borgnis, E. L., Turner, R. E., & Milan, C. S. (2012). Carbon sequestration and sediment accretion in San Francisco Bay tidal wetlands. *Estuaries and Coasts*, 35, 1163-1181.
25. Callaway, J. C., Parker, V. T., Vasey, M. C., Schile, L. M., & Herbert, E. R. (2011). Tidal wetland restoration in San Francisco Bay: history and current issues. *San Francisco Estuary and Watershed Science*, 9(3).
26. McKee, L., Lowe, J., Dusterhoff, S., Foley, M., and Shaw, S. (2020). Sediment Monitoring and Modeling Strategy. A technical report prepared for the Regional Monitoring Program for Water Quality in San Francisco Bay (RMP) Sediment Workgroup. SFEI Contribution No. 1016. San Francisco Estuary Institute, Richmond, California.

27. Dusterhoff, S; McKnight, K; Grenier, L; Kauffman, N. (2021). Sediment for Survival: A Strategy for the Resilience of Bay Wetlands in the Lower San Francisco Estuary. SFEI Contribution No. 1015. San Francisco Estuary Institute: Richmond, CA
28. Keller, B. R. (2009). Literature review of unconsolidated sediment in San Francisco Bay and nearby Pacific Ocean Coast. San Francisco Estuary and Watershed Science, 7(1).
29. Morris, G. L. (2020). Classification of management alternatives to combat reservoir sedimentation. Water, 12(3), 861.
30. Holmes, R., Milligan, B., Wirth, G. (2023). Silt Sand Slurry: Dredging, Sediment, and the Worlds We Are Making. Applied Research & Design.
31. USACE Dredged Material Management Office (DMMO) Annual Reports (2022).
32. Siu, J. (2023, September 15). "Dredging and Dredged Material Reuse Reflections" [Zoom Online PowerPoint presentation]. Sediment and Beneficial Reuse Commissioner Working Group for the Sediment Wetland Adaptation Project, San Francisco, CA.
33. Fernandez, X. and Halsing, D. (2023, November 17). "Terrestrial material reuse in restoration and SLR adaptation" [Zoom Online PowerPoint presentation]. Sediment and Beneficial Reuse Commissioner Working Group for the Sediment Wetland Adaptation Project, San Francisco, CA.
34. Baptist, M. J., Gerkema, T., Van Prooijen, B. C., Van Maren, D. S., Van Regteren, M., Schulz, K., ... & van Puijenbroek, M. E. B. (2019). Beneficial use of dredged sediment to enhance salt marsh development by applying a 'Mud Motor'. Ecological Engineering, 127, 312-323.
35. Thorne, K. M., Freeman, C. M., Rosencranz, J. A., Ganju, N. K., & Guntenspergen, G. R. (2019). Thin-layer sediment addition to an existing salt marsh to combat sea-level rise and improve endangered species habitat in California, USA. Ecological Engineering, 136, 197-208
36. Suedel, B. C., McQueen, A. D., Wilkens, J. L., Saltus, C. L., Bourne, S. G., Gailani, J. Z., ... & Corbino, J. M. (2021). Beneficial use of dredged sediment as a sustainable practice for restoring coastal marsh habitat. Integrated Environmental Assessment and Management, 18(5), 1162-1173.
37. Swanson, K. M., Drexler, J. Z., Schoellhamer, D. H., Thorne, K. M., Casazza, M. L., Overton, C. T., ... & Takekawa, J. Y. (2014). Wetland accretion rate model of ecosystem resilience (WARMER) and its application to habitat sustainability for endangered species in the San Francisco estuary. Estuaries and Coasts, 37, 476-492.
38. Parker, V. T., & Boyer, K. E. (2019). Sea-level rise and climate change impacts on an urbanized Pacific Coast estuary. Wetlands, 39, 1219-1232.
39. Buffington, K. J., Janousek, C. N., Dugger, B. D., Callaway, J. C., Schile-Beers, L. M., Borgnis Sloane, E., & Thorne, K. M. (2021). Incorporation of uncertainty to improve projections of tidal wetland elevation and carbon accumulation with sea-level rise. PLoS One, 16(10), e0256707.